

## WQ770-b Turbidity Meter



- Portable unit with completely submersible sensor
- Simple and convenient to use
- Marine grade cable with strain relief
- Rugged anodized aluminum sensor housing

### Applications

Applications include; water quality testing and management, river monitoring, stream measurement, reservoir water quality testing, groundwater measuring, water and wastewater treatment, effluent, and industrial control.

For environmental monitoring, the sensor is placed directly into a river or lake, and positioned where the turbidity is to be monitored. For process monitoring, the sensor can be inserted into low pressure pipes, for on-line monitoring, by using a standard 1.5" compression coupler.

### Description

The Global Turbidity Meter is a highly accurate device with a fully submersible sensor for in-situ environmental or process monitoring. The meter is provided with a padded carrying case and 10' of marine grade cable, with lengths up to 100' available upon request.

#### Method:

In accordance with USEPA Method 180.1 for turbidity measurement the sensor is a 90 degree scatter nephelometer where a focused beam is directed into the monitored water. The light beam reflects off particles in the water, and the resultant light intensity is measured by a photodetector positioned at 90 degrees to the light beam. The detected light intensity is directly proportional to the turbidity of the water. The WQ770 sensor utilizes a second light detector to correct for light intensity variations, color changes, and minor lens fouling.

#### Calibration:

All turbidity meters are factory calibrated to the highest standards and should not need recalibration for 6-12 months. User calibration, when required, is very easy using the step-by-step scaling process within the display unit.

### Specifications

*Range:* 0-50 NTU and 0-1000 NTU

*Accuracy:* ±5 % of full scale

*Resolution:* 12 bit

*Method:* Nephelometer with correction

*Power:* Internal 9VDC battery

*Warm-up Time:* 3 seconds minimum

*Operating Temperature:* -40° to +50°C

*Materials:* Black anodized aluminum, stainless steel, delrin, Sapphire optical windows, Polyurethane jacketed cable.

*Pressure:* 0-50 psi

*Light Source:* pulsed LED

*Cable Length:* Meter=10' standard (optional to 100')

*Sensor Size:* Body= 1 1/2"D x 8.5"L Sensor Shield= 1 1/2" x 2"

*Overall Length:* 9"

*Weight:* 2 lbs.

### Options and Accessories

#### WQ770-b Turbidity Meter

Includes sensor on 25' cable standard.

#### WOEXC Extra Cable

Cable length is measured from end of cable to bottom of sensor. After 25', up to 100'

Contact  
Global Water  
for all your  
instrumentation  
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



**Global Water**  
The Leader in Water Instrumentation

In the U.S. call toll free  
at 1-800-876-1172  
International: 916-638-3429  
Fax: 916-638-3270  
Email: globalw@globalw.com

Visit our online catalog at:  
www.globalw.com  
Our Address:  
11390 Amalgam Way  
Gold River, CA 95670